

AGILE MAX 109



PERFORMANCES	MAX 109 E	MAX 109 S
Hourly efficiency	9000 m ² /h	9000 m ² /h
Working width with central brush	700 mm	700 mm
Working width with 1 side brush	950 mm	950 mm
Working width with 2 side brushes	1200 mm	1200 mm
Autonomy	3 - 4 h	-
Maximum speed	7,5 km/h	7,5 Km/h
Work climbing ability	19%	19%
WASTE COLLECTION SYSTEM		
Hopper capacity	80 L	80 L
High dump	0-1400 mm	0-1400 mm
Waste collection with standard plastic bag	Sì	Sì
Filter surface	4 m ²	4 m ²
Electric filter shaker	24 V	24 V
TECHNICAL DATA		
Motor power & Supply	0,75 Kw Batteria 24 V	Honda 4.0 hp benzina - GPL kit
R.p.m. electric/engine motor	3000	3000
Traction	Electric 24 V	Electric 24 V
Steering range	1280 mm	1280 mm
Speed control system	Yes	Yes
Noise level	73 dB(A)	84 dB(A)
DIMENSIONS AND WEIGHT		
Dimensions:		
Length	1500 mm	1500 mm
Width	980 mm	980 mm
Height	1400 mm	1400 mm
Empty weight	365 kg	440 kg

AGILE MAX 108



MODELLO	MAX 108 E	MAX 108 S
Hourly efficiency	9000 m ² /h	9000 m ² /h
Working width with central brush	700 mm	700 mm
Working width with 1 side brush	950 mm	950 mm
Working width with 2 side brushes	1200 mm	1200 mm
Autonomy	3 - 4 h	-
Maximum speed	7,5 km/h	7,5 Km/h
Work climbing ability	19%	19%
WASTE COLLECTION SYSTEM		
Hopper capacity	70 L	70 L
High dump	-	-
Waste collection with standard plastic bag	Sì	Sì
Filter surface	4 m ²	4 m ²
Electric filter shaker	24 V	24 V
TECHNICAL DATA		
Motor power & Supply	0,75 Kw Batteria 24 V	Honda 4.0 hp benzina - GPL kit
R.p.m. electric/engine motor	3000	3000
Traction	Electric 24 V	Electric 24 V
Steering range	1280 mm	1280 mm
Speed control system	Yes	Yes
Noise level	73 dB(A)	85 dB(A)
DIMENSIONS AND WEIGHT		
Dimensions:		
Length	1400 mm	1400 mm
Width	980 mm	980 mm
Height	1220 mm	1220 mm
Empty weight	280 kg	290 kg

The technical data are indicative and can be changed without notice.

Authorized dealer

AGILE MAX 109

AGILE MAX 108



POWER AT HAND

A unique feature of this sweeper is the extreme maneuverability. Equipped with MP-HT **metal frame**, which gives great solidity and compactness, AGILE moves surprisingly in confined spaces. Thanks to the front wheel drive, it is able to steer almost on itself, so as to get out of tight places even without entering the reverse gear.


NEW THREE-PHASE AC MOTOR

Greater autonomy: with the new three-phase AC motor with low energy absorption, the battery lasts longer.

More power: it allows to work on steep ramps and for long distances without overloading engine.

Higher sensitivity: higher engine performance, responds in a very sensitive way to the operator's commands, without tearing.

Less maintenance.
Less operating costs.



METAL FRAME



FOR WAREHOUSES
AND CORRIDORS



WASTE
IN BAG

AGILE MAX 109



HYDRAULIC ARM

It is possible to unload directly inside a container (the height dump system can be installed in a later time as an added kit).

WASTE IN BAG

The collection system in standard garbage bags, easily replaceable, greatly simplifies the emptying of the machine and protects the operator from contact with dust.

AGILE MAX 108



COLLECTION IN BAGS

The dirt is collected directly in two disposable bags placed in the container with rollers. This system protects the operator from contact with dust during the emptying of the machine, and avoids the lifting of excessive loads.



HIGHT POSITIONED FILTER WITH CYCLONE CHAMBER

The filter, easily accessible, is positioned above the cyclonic chamber: it remains far from dust and humidity and remains efficient longer. It is also easy to keep clean thanks to the electric filter shaker.



ERGONOMICS

Easy to use even for non-specialized operators. The driving position and the maneuverability make the job easy and comfortable. It does not require a drive license.



DUST CONTROL KIT WITH WATER

The water spray system on the brushes avoids raising dust while working. A disinfectant can be added into the water tank to increase the effectiveness of the cleaning.



EASY MAINTENANCE

Cleaning or changing the filter or brushes is extremely easy and fast. It is possible to place the machine vertically to have full access to the base of the sweeper without any need for a lifter.



ANTI-SHOCK BRUSHES

The brushes are mounted on elastic supports and retract on contact with an obstacle even near walls and shelves.



TYPES OF FILTERS

- Three types of filters are available:
- paper panel standard
- panel polyester for wet powders
- bag filters for the toughest jobs.



EASY TO TRANSPORT

It can be transported easily even in a small van.



WORK IN SLOPE

It can also work on sloping surfaces and steep ramps (up to 19%).



FEED

- PETROL
- LPG
- ELECTRIC



STEERING WHEEL DRIVE

Allows tight bending radius and ensures great maneuverability.



SEE YOURSELF SIMPLICITY OF USE OF AGILE

<https://youtu.be/zEVQCbDnUes>