



## JH 30 G plus EX - hydraulic jack without integrated pump unit

Load capacity: 30 t

Stroke: 200 mm

Art.-Nr. 11 630 106-G

### Advantages of jacks – Series JH G plus EX

- Integrated spring return retracts piston automatically on JH 15 up to JH 30 G plus EX.
- Slide shoe design inside the guiding track prevents twisting of the piston inside the lifting cylinder. This guarantees better force distribution, less friction and reduced wear compared to conventional jacks.
- Reduced maintenance costs due to removable stroke unit and easy to change slide shoes.
- Extremely lightweight with high performance due to the use of high quality material and innovative design.
- Continuous adjustment to the load due to swiveling safety toe. Secure stability in every situation even in lifted position.

Here you find an [application video](#).

## Technical data

Title	Unit	Data
Load capacity on top plate	kg	30000
Stroke	mm	200
Minimum lift toe height	mm	20
Maximum lift toe height	mm	305
Lift toe adjustment	mm	5 x 71
Top plate height	mm	420
Toe width front	mm	80
Toe depth	mm	66
Length feet in front	mm	380

<b>Title</b>	<b>Unit</b>	<b>Data</b>
Length feet on side	mm	270
Width	mm	375
Height	mm	420
Cylinder volume	L	1,27
Weight	kg	92