FRANK[®]

Dry Steam Cleaner



iSteam iS80 oil-heated

The iS80 dry steam cleaner of the iSteam series is oil-heated and impresses with its strength and performance. The innovative continuous heating system has a significantly higher power level than boiler systems and thus achieves faster steam generation. Due to the ergonomically shaped steam gun and the constant pressure, they are popular for continuous operation. Various functions can be controlled via the integrated remote control on the steam gun: start/ stop, cleaning additives on/off and heating on/off.

Steam pressure	10 bar
Steam temperature	170 - 180°C
Steam mass flow	78 - 168 kg/h
Heating capacity	80 kW

- Mobile 80 kW heating capacity
- **Efficient heating oil technology**


Stop & Go function

• The unit stops immediately when the pistol grip is released

- Suitable for continuous operation
 - No pressure loss due to heating coil technology
 - Ergonomically shaped steam gun


- Continuously adjustable steam quality (dry/wet)
- Extensive accessories and safety package
 - Particularly suitable for:
 - Degreasing of various materials
 - Machine maintenance
 - Basic cleaning for extreme soiling
 - Fire restoration

Water boiler system



Heating elements in the water cause it to evaporate under pressure. The steam is led upwards to the consumer.

Continuous flow heating system



The water flows through the heating coil and is heated by the heating wire. Before it exits, the water turns into steam and can be pumped on to the consumer.

Easy to maintain

Standard ac	cessories			
Steam hose	Round brush Ø60mm	Round brush Ø60mm Brass	Triangular brush	Industrial lance
	ALL DE COMPANY	ALAMINIAN .	1 Control	
Item No. 1506627	Item No. 1305770	Item No. 1305771	Item No. 1305769	Item No. 1507000
Industrial lance	Limescale protection			
ltem No. 1506899	Item No. 1502499			
Optional acc	cessories			
Steam hose 10m extension	Industrial lance	Industrial lance	Industrial lance	Industrial lance
O				
Item No. 1508314	Item No. 1305643	Item No. 1305760	Item No. 1305661	Item No. 1305761
Remote control unit	Remote control unit			



Item No. 1508001 Connection cable with plug: 5m Toggle switch for steam release Toggle switch for steam Toggle switch for detergent



Connection cable with plug: 5m
Toggle switch for steam release
Toggle switch for steam

Item No. 2103532

Technical data and equipment	
Operating pressure max.	10 bar
Steam mass flow max.	78 - 168 kg/h
Steam temperature max.	170 - 180°C
Electrical connection	1Ph / 230V / 50hz
Heating capacity	80 kW
Water supply	Water Mains connection
Detergent dosage	optional
Oil tank	23 litres
Weight	180 kg
Dimensions LxWxH (mm)	1245×590×910

CE

Technical changes and errors reserved

FRANK Hochdruck- & Dampftechnologie GmbH Bochumer Straße 15, D-57234 Wilnsdorf +49 (0) 2739-4 7993 0 info@frank-hdr.de www.frank-hdr.de



Robust

Easy to maintain