FRANK®

Dry steam cleaner



mSteam mS10

electrically heated


Constant steam volume, a variably adjustable steam quantity and an ergonomically shaped steam gun with remote control characterise the dry steam cleaners of the mSteam series. The electric steam cleaner is equipped with an industrial hose and mains water connection. The innovative continuous heating rod system also ensures a significantly higher efficiency compared to boiler systems.

Steam pressure	5 bar
Steam temperature	145°C
Steam mass flow	12 - 23 kg/h
Heating capacity	9,6 kW

- Innovative continuous heating rod system
- Higher steam output compared to boiler technology
- Faster steam generation compared to boiler systems
- More energy efficient than boiler systems
- Designed for continuous operation
 - No pressure loss
 - Ergonomic designed pistol grip with remote control for steam ON/OFF and optional detergent dosage ON/OFF
- Powder-coated Cover (optional available in stainless steel)


- Industrial hose connection
- Mains water connection
- Integrated water softening system
- Adjustable steam quality (wet/drv)
- Industrial accessories and security package
- Ideally suited for:
 - Food industries
 - FRANK belt sanitation systems
 - Machine maintenance
 - Deep cleaning and de-greasing
 - Decontaminating and sanitising

Principle water boiler



Heating elements in the water cause it to evaporate under pressure. The steam is led upwards to the consumer.

Principle instantaneous water heater



The water flows through the heating coil and is heated by the heating wire. Before exiting, the water turns into steam and can be pumped on to the consumer.

Standard accessories

Steam hose

6m with hand grip



A-+ Nr 1506607

Nylon

Δrt Nr 13057

Round brush Ø60mm Round brush Ø60mm



Art Nr 13057

Triangluar brush

Nvloi



Art. Nr. 1305769





VS Spray lance

50cm with flat jet nozzle



Art. Nr. 1503379

Water softener cartridge



Optional accessories

Steam hose

10m extension



Art. Nr. 1508314

Remote control



Art. Nr. 1508001

- Connection cable with plug: 5m ■ Toggle switch for steam release
- Toggle switch for steam
 Toggle switch for detergent

Remote control



Art. Nr. 2103532

- Connection cable with plug: 5m
- Toggle switch for steam release
 Toggle switch for steam

Technical data and features	
Operating pressure	2 - 5 bar
Steam mass flow max.	12 - 23 kg/h
Steam temperature max.	155°C
Electrical connection	3Ph / 400V / 50hz
Heating capacity	9,6 kW
Weight	145 kg
Dimensions LxWxH (mm)	1070×415×950

Technical changes and errors excepted

