

# Grass collector

## - Park Ranger 2150







3100 mm

#### Standard equipment:

**Hydraulic tipping** Easy emptying of the hopper without leaving the cabin.

Hydraulic tipping function and automatic lid opening. With a tipping hight of 1800 mm it can be emptied

directly into a container.

**Two-piece suction hose** The two-piece suction hose ensures easy access in

case of clogging.

Air intake A special air intake on both sides of the hopper protects

the engine of the utility machine against grass dust.

**Safety valve**A safety valve makes sure to stop both turbine and rotary mower while the hopper is being emptied.

Stand A stand for easy and quick attaching/detaching of the

hopper is standard equipment.

#### **Extra equipment (options):**

**Mulch and rotary mower** You can quickly convert the grass collector to a non**kits** collecting mulch mower or standard rotary mower with

the help of special kits available.

the help of opeolal Nito available.

**Leaf suction unit** The grass collector can also be combined with the leaf

suction unit for easy collection of leaves.

### **Technical specifications**

Difficitations				
ī	enath	(with		

Length (with mower 1000)	mm	3100
Width (with mower 1000)	mm	1100
Height with cabin	mm	1950
Storage dimensions		
Length	mm	1700
Width	mm	1050
Height	mm	2000
Weights		
Weight with / without cabin 1)	kg	995 / 885
Payload with / without cabin	kg	305 / 415
Weight (grass collector)	kg	170
Weight (frame)	kg	31
Hopper (grass collector)		
Hopper volume	1	470
Hopper load, max.	kg	120
Tipping height	mm	1800
Performance		
Air flow	m³/h	1500
Air speed	km/h	70
Max. recommended operating speed	km/h	8-10
Noise level		
Noise level LwA (2000/14/EC)	dB(A)	105
CE certified according to EU directive		
1) Includes: grass collector, mower 1000, 75 kg operator :	and 90% fuel capacity.	

<sup>1)</sup> Includes: grass collector, mower 1000, 75 kg operator and 90% fuel capacity.





