

TIN KNOCKER TK POWER CRIMPER BEADER

HERE IS THE BEEF AND THROAT DEPTH YOU NEED

This is a versatile, workhorse of a machine. With a 13" throat and capacity of 18-gauge mild steel, it can perform most all beading and swaging functions. It is a beefy ¾ HP machine, with the business end made of solid, machined cast iron, mounted on a sturdy sheet metal cabinet. A two-pedal foot switch allow the operator to have two hands free at all times when changing direction of the rolls. An enlarged back gauge plate also facilitates handling of the part. Includes spacer collars for all operations except flanging. Rolls on this machine are interchangeable with the Roper Whitney Pexto 3617 rolls.

SPECIFICATIONS

Maximum Capacity mild steel or equivalent	18-gauge mild steel
Throat to Frame Depth	13"
Throat to gauge depth	12.25"
Distance between shaft centers	3"
Shipping weight	340 lbs.
Motor	1 hp, 230V, 3 phase
Dimensions	L 39" x H 52" x W 14.5"

Other Options:

Single Phase VFD

Air Cylinder Pressure Control



Optional Air Over System

Tooling Includes:

Crimper & Bead Combo, Small Crimp, Large Crimp, Ogee Bead, Single Bead, Offset, Turning, Wiring, Elbow Edging.

TAAG INDUSTRIES CORP.
1550 SIMPSON WAY, ESCONDIDO, CA 92029
Tel: (800) 640-0746 Fax: (760) 727-9948
Website: www.tinknocker.com Email: info@taagind.com